

DECLARATION OF PERFORMANCE

No: PB-YSGK-062013/03

1. Identification of Product: PB-YSGK-062013/03 - Dry pressed ceramic floor tile, Eb $\leq 0,5$ % Group B1a GL, UGL – Ek G

2. Intended Use(s): For used as floor and wall covering in interior and exterior spaces.

3. Manufacturer:

Yurtbay Seramik San. ve Tic. A.Ş.

Oklubarlı Mh. No:22 26670 İnönü Eskisehir/TÜRKİYE

Tel: +90 222 596 62 00

Fax:+90 222 596 61 99

www.yurtbayseramik.com

info@yurtbayseramik.com

4. Authorized Representative: Yurtbay Seramik San. ve Tic. A.Ş

5. System(s) for evaluating and verifying constancy of performance: System 4

6. Harmonized Standard: EN 14411:2016

7. Declared Performance:

Essential Characteristics	Performance	Harmonised Technical Specification
Reaction to Fire	A1FL	
Breaking Strength	Thickness ≥ 7.5 mm. ≥ 1300 N Thickness <7.5 mm. ≥ 700 N	
Flexural Strength	≥ 35 N/mm ²	
Release of Dangerous Substance	Company Declared Value	
-Cadmium	$\leq 0,03$ mg/dm ² Cd	
-Lead	$\leq 0,2$ mg/dm ² Pb	
Thermal Shock Resistance	Pass	EN 14411:2016
Slipperiness	NPD	
Bond Strength/Adhesion		
Cementitious adhesive, type C2	Min. 1 N/mm ²	
Durability		
-Internal Use:	Pass	
-External Use: Freeze-Thaw Resistance	Pass	

The building material described above has the declared performance group. This performance declaration prepared in accordance with the Construction Products Directive (305/2011/EU) is published only under the responsibility of the manufacturer defined above.

Signed for and on behalf of the manufacturer by:

YURTBAY
SERAMİK SAN.TİC.A.Ş.

A.Cengiz ALAN
Quality Assurance Director
İnönü/Eskişehir, 01.12.2023

