

COMMUNICATION

Wi-Fi Protocol	IEEE 802.11b/g/n
Wi-Fi Frequency	2.4 GHz Wi-Fi

TECHNICAL SPECIFICATIONS

Form Factor	A60, E27
Brightness	806 Lumens
Color Temperature Range	2500-6500 K
Color Changing	Yes (via app and cloud only)
Dimmable	Yes (via app and cloud only)
Light Beam Angle	220 °
Color Rendering Index	≥ 80
Warm-Up Time to 95%	≤1 s
SDCM	≤ 6
Switching Cycles	15,000
Lifetime	25,000 Hrs
Input Voltage	220-240 V~, 50/60 Hz
Weighted Energy Consumption	8.7 kWh/1000h
Max. Power Consumption	8.3 W
Standby Power Consumption	0.4 W
Equivalent Incandescent Lamp Power	60 W
Energy Class	F
Warm-up Time up to 95%	≤1 s
Colour Rendering Index	≥ 80
Switching Circles	15,000

ALLGEMEIN

Verpackungsinhalt	1. Tapo L530E 2. Quick Start Guide
Sockel	EU/TW Version: E27 US/KR/JP Version: E26
Reference Control Settings	2700K, 100% brightness (factory default settings) Refer to Factory Reset in the user guide to reset this product to the factory default settings
Abmessungen (H*B*T)	115 × 60 mm
Lifetime	15,000 Hrs

BETRIEBSZUSTAND

Input	220–240 V, 50/60 Hz, 73 mA
Typische Leuchtstärke	806 lumens
Leistungsaufnahme in Watt	8.7 W

BETRIEBSZUSTAND

Farbtemperatur	2,500 K~6,500 K
Strahlwinkel	220 degrees
Dimmbar	Yes

PHYSICAL

Package Content	• Tapo Smart Light Bulb • Quick Start Guide
Dimensions (W x D x H)	115 × 60 mm

SONSTIGES

Zertifizierung	CE, ERP, RoHS, SAA, RCM
Umgebung	• Operating Temperature: -15 °C~40 °C • Operating Humidity: 10%~90%RH, Non-condensing
Works with Google Home	Yes
Works with Amazon Alexa	Yes
Wireless Connectivity	IEEE 802.11b/g/n, 2.4 GHz band only