

HARDWARE-FUNKTIONEN

Standards und Protokolle	IEEE 802.3i/802.3u/ 802.3ab/802.3x, IEEE 802.1p
Schnittstelle	5 10/100/1000Mbps, Auto-Negotiation, Auto-MDI/MDIX Ports
Anzahl Lüfter	Fanless
Energieverbrauch	Maximum: 2.43W(220V/50Hz)
Externe Spannungsversorgung	External Power Adapter (Output: 9VDC / 0.6A)
LED	System Power Link/Act indicators per port built into each RJ-45 port
Abmessungen (B*T*H)	3.9 x 3.9 x 1.0 in. (100 x 98 x 25 mm)

PERFORMANCE

Paketweiterleitungsrate	7.4Mpps
MAC-Adresstabelle	2K
Paketpufferspeicher	1Mb
Jumbo-Frames	16KB

SOFTWARE-FUNKTIONEN

Erweiterte Funktionen	Green Technology 802.3X Flow Control 802.1P/DSCP QoS (for V2 and later version) IGMP Snooping
Übertragungsmethode	Store and Forward

SONSTIGES

Zertifizierung	CE, FCC, RoHS
Verpackungsinhalt	5-Port 10/100/1000Mbps Desktop Switch Power Adapter Installation Guide Rubber Feet
Umgebung	Operating Temperature: 0°C~40°C (32°F~104°F) Storage Temperature: -40°C~70°C (-40°F~158°F) Operating Humidity: 10% ~ 90% non-condensing Storage Humidity: 5%~90% non-condensing