

HARDWARE-FUNKTIONEN

Standards und Protokolle	HomePlug AV2, HomePlug AV, IEEE 1901, IEEE 802.3, IEEE 802.3u, IEEE 802.3ab
Steckertyp	EU, UK, US
Schnittstelle	Gigabit Ethernet Port
Taste	Pair/Reset button
Energieverbrauch	Maximum: 2.7W (220V/50Hz) Typical: 2.3W (220V/50Hz) Standby: 0.5W (220V/50Hz)
LED	PWR, PLC, ETH
Abmessungen (B*T*H)	2.6*2.0*1.1 in (65*52*28.5mm)
Reichweite	300 Meters over electrical circuit

SOFTWARE-FUNKTIONEN

Modulationsverfahren	OFDM (PLC)
Verschlüsselung	Powerline Security: 128-bit AES

SONSTIGES

Zertifizierung	CE, RoHS
Verpackungsinhalt	Powerline Ethernet Adapter 6.5 ft. (2 m) Ethernet cable (RJ45) Quick Installation Guide
Systemanforderungen	Windows 2000/XP/2003/Vista, Windows 7/8/8.1, Mac, Linux
Umgebung	Operating Temperature: 0°C~40°C (32°F ~104°F) Storage Temperature: -40°C~70°C (-40°F ~158°F) Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing