

KAMERA

Bildsensor	1/2.8" Progressive Scan CMOS Not Starlight Sensor
Linse	Focal Length: 3.15mm Aperture: F2.0 Field of View: 129.4° (Diagonal), 107.6°(Horizontal), 57.6°(Vertical)
Night Vision	850 nm IR LED (30 ft / 9 m)
Lighting	/
Hub Compatibility	/
Interface & Button	1× RESET Button 1× MicroSD Card Slot (Up to 512GB)
Pan/Tilt Range	/

HUB

Device Compatibility	/
Connection Capacity	/
Interface & Button	/

VIDEO & AUDIO

Maximum Resolution	2K 3MP (2304 × 1296 px)
Frame Rate	15 fps
Digital Zoom	/
Video Compression	H.264
Live View	Yes
Image Enhancement	3D DNR WDR
Audio Input & Output	Built-in Microphone and Speaker
Audio Communication	Two-Way Audio with Noise Cancellation
Siren Volume	89dB (Level measured at 4-inch/10-cm distance)

STORAGE

Local Storage	MicroSD Card Slot on Camera (Up to 512 GB) General Information about using MicroSD Cards >
Cloud Storage	Tapo Care Cloud Storage Services (Subscription required)

DETECTION AND NOTIFICATIONS

Sensor	/
AI Detection	Motion Detection Person Detection BabyCry Detection
Activity Zones	Yes
Output Notification	System Notification System Notification with Snapshot (Tapo Care Services)

NETZ

Network Connectivity	Connect via Wi-Fi
Wireless Connectivity	IEEE 802.11b/g/n, 2.4 GHz Wi-Fi
Ethernet Port	/
RTSP	Yes
ONVIF	Yes

SICHERHEIT

Security	On-Device Machine Learning 128-bit AES Encryption with SSL/TLS WPA/WPA2-PSK
----------	---

POWER

Power Source	9V DC Power Adapter
Input Voltage	100-240 V, 50/60 Hz
Output Voltage	9 V, 0.6 A (DC Power)

ALLGEMEIN

Smart Integration	Google Assistant, Amazon Alexa
Mounting Options	Tabletop Ceiling-Mounted
Operating Temperature	0°C~40°C
Storage Temperature	-20°C~60°C
Operating Humidity	10%~90% RH, Non-condensing
Storage Humidity	5%~90% RH, Non-condensing
Dimensions (W x D x H)	2.66 × 2.15 × 3.89 in (67.6 × 54.6 × 98.9 mm)
Verpackungsinhalt	Tapo C110 Camera DC Power Adapter Quick Start Guide Mounting Screws Mounting Template Mounting Anchors
Certifications	/