

KAMERA

Bildsensor	1/2.9" Progressive Scan CMOS Starlight Sensor
Linse	Focal Length: 2.45mm Aperture: 2.0 Field of View: 140°(Diagonal), 120°(Horizontal), 67°(Vertical)
Night Vision	850 nm IR LED (30 ft / 9 m) 940 nm IR LED (30 ft / 9 m)
Lighting	/
Hub Compatibility	/
Interface & Button	1× RESET Button 1× MicroSD Card Slot (Up to 512 GB)
Pan/Tilt Range	/

HUB

Device Compatibility	/
Connection Capacity	/
Interface & Button	/

VIDEO & AUDIO

Maximum Resolution	2K QHD 4MP (2560 × 1440 px)
Frame Rate	15/20/25/30 fps (Default 15fps)
Digital Zoom	12x
Video Compression	H.264
Live View	Yes
Image Enhancement	3D DNR WDR HDR
Audio Input & Output	Built-in Microphone and Speaker
Audio Communication	Two-Way Audio with Noise Cancellation
Siren Volume	94dB (Level measured at 4-inch/10-cm distance)

STORAGE

Local Storage	MicroSD Card Slot on Camera (Up to 512 GB) General Information about using MicroSD Cards >
Cloud Storage	Tapo Care Cloud Storage Services (Subscription required)

DETECTION AND NOTIFICATIONS

Sensor	/
AI Detection	Motion Detection Person Detection Line-Crossing Detection Tamper Detection BabyCry Detection Vehicle Detection Pet Detection Meow Detection Bark Detection Glass-Breaking Detection

DETECTION AND NOTIFICATIONS

Activity Zones	Yes
Output Notification	System Notification System Notification with Snapshot (Tapo Care Services)

NETZ

Network Connectivity	Connect via Wi-Fi
Wireless Connectivity	IEEE 802.11b/g/n/ax, 2.4 GHz Wi-Fi; BLE
Ethernet Port	/
RTSP	Yes
ONVIF	Yes

SICHERHEIT

Security	On-Device Machine Learning 128-bit AES Encryption with SSL/TLS WPA/WPA2-PSK/WPA3
----------	--

POWER

Power Source	9V DC Power Adapter
Input Voltage	100-240 V, 50/60 Hz
Output Voltage	9.0 V, 0.6 A (DC Power)

ALLGEMEIN

Smart Integration	Google Assistant, Amazon Alexa, Apple HomeKit
Weather Resistance	/
Mounting Options	Tabletop Ceiling-Mounted
Operating Temperature	0°C~40°C
Storage Temperature	-20°C~60°C
Operating Humidity	10%~90% RH, Non-condensing
Storage Humidity	5%~90% RH, Non-condensing
Charging Temperature	/
Dimensions (W x D x H)	3.01 × 2.61 × 1.76 in (76.4 × 66.4 × 44.6 mm)
Verpackungsinhalt	Tapo C125 Camera Power Adapter Mounting Screws Mounting Template Mounting Anchors Metal Plate 3M Adhesive Quick Start Guide
Certifications	/