

KAMERA

Bildsensor	1/2.9" Progressive Scan CMOS Starlight Sensor
Linse	Focal Length: 4.3 mm Aperture: F1.6 Field of View: 100° (Diagonal), 83°(Horizontal), 43°(Vertical)
Night Vision	1 × 850 nm IR LED (30 ft / 9 m) 2 × 940 nm IR LED (30 ft / 9 m)
Lighting	/
Hub Compatibility	/
Interface & Button	1× RESET Button 1× Privacy Button 1× MicroSD Card Slot (Up to 512 GB)
View Range	360° Horizontal, 149° Vertical
Pan/Tilt Range	Pan Mechanical Range: (360° Pan Coverage) Tilt Mechanical Range: (149° Tilt Coverage)

HUB

Device Compatibility	/
Connection Capacity	/
Interface & Button	/

VIDEO & AUDIO

Maximum Resolution	2K QHD 4MP (2688 × 1520 px)
Frame Rate	15/20/25/30 fps (Default 15fps)
Digital Zoom	None
Video Compression	H.264
Live View	Yes
Image Enhancement	3D DNR WDR HDR
Audio Input & Output	Built-in Microphone and Speaker
Audio Communication	Two-Way Audio with Noise Cancellation
Siren Volume	98dB (Level measured at 4-inch/10-cm distance)

STORAGE

Local Storage	MicroSD Card Slot on Camera (Up to 512 GB) General Information about using MicroSD Cards >
Cloud Storage	Tapo Care Cloud Storage Services (Subscription required)

DETECTION AND NOTIFICATIONS

Sensor	/
AI Detection	Motion Detection Person Detection Line-Crossing Detection Tamper Detection BabyCry Detection Vehicle Detection Pet Detection Meow Detection

DETECTION AND NOTIFICATIONS

	Bark Detection Glass-Breaking Detection
Activity Zones	Yes *Only works with Motion Detection.
Output Notification	System Notification System Notification with Snapshot (Tapo Care Services)

NETZ

Network Connectivity	Connect via Wi-Fi
Wireless Connectivity	IEEE 802.11b/g/n/ax, 2.4 GHz Wi-Fi
Ethernet Port	/
RTSP	Yes
ONVIF	Yes

SICHERHEIT

Security	On-Device Machine Learning 128-bit AES Encryption with SSL/TLS WPA/WPA2-PSK/WPA3
----------	--

POWER

Power Source	12V DC Power Adapter Power consumption in networked standby: 1.34 W Power consumption in networked standby when all wireless network ports are activated: 1.34 W The default period of time after which the power management function switches the equipment automatically into a condition providing networked standby or low power mode: 20 minutes
Input Voltage	100-240 V, 50/60 Hz
Output Voltage	12 V, 1.0 A (DC Power)

ALLGEMEIN

Smart Integration	Google Assistant, Amazon Alexa, Apple HomeKit
Weather Resistance	/
Mounting Options	Tabletop Ceiling-Mounted
Operating Temperature	0°C~40°C
Storage Temperature	-20°C~70°C
Operating Humidity	10%~90% RH, Non-condensing
Storage Humidity	5%~90% RH, Non-condensing
Charging Temperature	/
Dimensions (W x D x H)	3.15 × 3.15 × 4.41 in (80 × 80 × 112 mm)
Verpackungsinhalt	Tapo C225 Camera DC Power Adapter Quick Start Guide Mounting Screws Mounting Template Camera Base
Certifications	CE,FCC,NCC,BSMI,IC,VCCI,JRF,KC,RCM,NTRA,Homekit,WEEE,EAC,RoHS

PACKAGE CONTENT

Package Content	Tapo Pan/Tilt Home Security Wi-Fi Camera Power Adapter Quick Start Guide Mounting Screws Mounting Plate Camera Base
-----------------	--