

NETZ

Systemanforderungen	Android 5.0 or higher, iOS 10 or higher
WLAN-Typ	Smart Radiator Valve: 868 MHz Kasa Hub: 2.4 GHz Wi-Fi, 868 MHz

ALLGEMEIN

Operating Temperature	0 °C ~ 40 °C (32 °F ~ 104 °F)
Operating Humidity	10%~90% RH, Non-condensing
Abmessungen (H*B*T)	Smart Radiator Valve $\varnothing 56.5 \times 84$ mm ($\varnothing 2.2 \times 3.3$ in) Kasa Hub 72×70.3×51 mm (2.8×2.7×2 in)
Material	PC
Tasten	Smart Radiator Valve: Control Knob, SYNC/Reset Button Kasa Hub: SYNC/Silence Button
Leistungsanforderungen	Smart Radiator Valve: 3.0V DC (2 x AA/LR6 batteries) Kasa Hub: AC, 100-240 V, 50/60 Hz
Certifications	CE, UKCA, RoHS

PACKAGE CONTENT

Package Content	1× KE100 1× KH100 2× AA/LR6 batteries 1× RA adapter 1× RAV adapter 1× RAVL adapter 1× CAL Adapter 1× M28 Adapter 1× GIA Adapter Quick Start Guide
-----------------	--