

KAMERA

Bildsensor	1/3"
Linse	F/NO: 1.61±10%; Focal Length: 3.18mm±5% Field of View: 113° (Diagonal), 97° (Horizontal), 54° (Vertical)
Night Vision	850 nm IR LED up to 49 ft/15m
Betrachtungswinkel	113°
Auflösung	2K QHD 4 MP (2560 × 1440 px)

AUDIO

Audiokommunikation	2-way audio
Audio Input & Output	Built-in microphone and speaker

NETZ

Protokoll	TCP/IP, ICMP, DNS, HTTPS, TCP, UDP
Wireless Security	WPA/WPA2-PSK
Wi-Fi Protocol	IEEE 802.11b/g/n, 2.4 GHz
Frequency	2.4 GHz

ACTIVITY NOTIFICATIONS

Input Trigger	Motion detection, Person detection, Pet detection, Vehicle detection.
Output Notification	Notification, Snapshot(Tapo care), Clips(Tapo care).

HARDWARE

Button	Camera Button: Reset/SYNC Button Hub Button: Reset Button; SYNC Button
Indicator LED	Camera Indicator LED: System LED Hub Indicator LED: System LED
Adapter Input	Camera Adapter Input: 100-240V, 50/60Hz Hub Adapter Input: 100-240V, 50/60Hz, 0.3A
Adapter Output	Camera Adapter Output: 5.0V, 1.0A Hub Adapter Output: 9.0V, 0.85A
Dimensions (W x D x H)	Camera Dimensions: 4.35 x 2.52 x 2.52in. (110.6*64.2*64.2mm) Hub Dimensions (L x W x H): 2.8 x 2.8 x 1.2 in. (71.45*71.45*31.25mm)

VIDEO/BILD

Videokompression	H.264
Framerate und Auflösungen	15/20 fps
Videostreaming	2K QHD

PACKAGE CONTENT

Package Content	Tapo C420 Cameras (Battery Included) - micro-USB Tapo H200 Hub USB Adapter USB Adapter Cable
-----------------	---

PACKAGE CONTENT

	DC Power Adapter Mounting Screws Mounting Templates Camera Brackets Quick Start Guide RJ45 Ethernet Cable
--	--

ENVIRONMENT

Operating Temperature	-20°C~45°C(-4°F ~113 °F)
Storage Temperature	-20°C~60°C (-4°F~140°F)
Operating Humidity	10%~90%RH, Non-condensing
Storage Humidity	5%~90%RH, Non-condensing