



DECLARATION OF PERFORMANCE No. 001.NAT-2013

1.- Unique identification code of product type

Type, batch or serial number or any element allowing identification of the product

Extruded ceramic tiles, with water absorption $E_b \leq 0,5\%$

2.- Intended use(s)

For internal and external walls and floorings

3.- Name or registered trade mark, and contact address of the manufacturer

NATUCER, S.L. Calle Les Forques, nº 2, 12200 Onda (Castellón) Spain

4.- System(s) of assessment and verification of constancy of performance (AVCP)

System 4

5.- Name and identification number of notified laboratory, if relevant

Not relevant

6.- Declared performances

Essential characteristics	Performance	Harmonized technical specification
Reaction to fire:	Clase A1fl - A1	EN 14411:2012
Release of dangerous substance for:		
-Cadmium	NPD	
-Lead	NPD	
Breaking strength:	>1300 N	
Slipperiness, as:		
PTV (wet) slider 57, CEN/TS 16165:2012 Annex C	NPD	
Bond strength/adhesion, for:		
Cementitious adhesive, type C2	> 1,0 N/mm ²	
Thermal shock resistance	Pass	
Durability for:		
-internal use:	Pass	
-external use; freeze-thaw resistance	Pass	
Tactility:	NPD	

The performance of the product identified in point 1 is conformity with the declared performances in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Signed for and on behalf of manufacturer by:

Date: 1 July 2013

Name: Javier Rubert Andrés

Function: Director Técnico