



Declaration of performance

No. 001PBA2013-07-01

1. Unique identification code of the product type
Type, batch or serial number or any other element allowing identification of the product
**Dry-pressed ceramic tiles, with water absorption $E_b \leq 0,5\%$
72.05095 – PIRITE DARK 30,5X61**
2. Intended use(s)
For internal and external floorings
3. Name and registered trade mark, and contact address of the manufacturer
ITA Spa, via XXV Aprile 12, I – 42013 Salvaterra di Casalgrande (RE)
4. Declared performance

Essential characteristics	Performance	Harmonised technical specifications
Reaction to fire	A1FL	EN 14411 : 2012
Breaking strength	> 35 N/MM2	
Thermal shock resistance	PASS	
Tactility	NPD	
Durability for:		
- internal use:	PASS	
- external use: freeze-thaw resistance	PASS	

The performance of the product identified in point 1 is in conformity with the declared performances in point 4.
This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Signed and on behalf of the manufacturer by:

Andrea Spagni

Fiorano Modenese, 09/12/2020

Name and function

Place and date of issue

ITA
CERAMICHE
Sede amministrativa / operativa:
Via Viazza Primo Tronco, 30 - 41042 Fiorano Mod.se (MO)
Sede legale: Via Idebrando Pizzotti, 2 - 42124 Reggio Emilia
Partita IVA: 02220550350 - **Signature**





Declaration of performance

No. 001PBA2013-07-01

1. Unique identification code of the product type
Type, batch or serial number or any other element allowing identification of the product
**Dry-pressed ceramic tiles, with water absorption $E_b \leq 0,5\%$
72.05090 – PIRITE GREY 30,5X61**
2. Intended use(s)
For internal and external floorings
3. Name and registered trade mark, and contact address of the manufacturer
ITA Spa, via XXV Aprile 12, I – 42013 Salvaterra di Casalgrande (RE)
4. Declared performance

Essential characteristics	Performance	Harmonised technical specifications
Reaction to fire	A1FL	EN 14411 : 2012
Breaking strength	> 35 N/MM ²	
Thermal shock resistance	PASS	
Tactility	NPD	
Durability for:		
- internal use:	PASS	
- external use: freeze-thaw resistance	PASS	

The performance of the product identified in point 1 is in conformity with the declared performances in point 4.
This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Signed and on behalf of the manufacturer by:

Andrea Spagni

Fiorano Modenese, 09/12/2020

Name and function

Place and date of issue

ITA
CERAMICHE
Sede amministrativa / operativa:
Via Viazza Primo Tronco, 30 - 41042 Fiorano Mod.se (MO)
Sede legale: Via Ildebrando Pizzetti, 2 - 42124 Reggio Emilia
Partita IVA: 02220550350 -
Signature

