



中国认可  
检验  
INSPECTION  
CNAS IB0071



NO.2618090135

# SAFETY DATA SHEET

**Product Name:** Rechargeable Li-ion Battery BT 60 Li  
4.0, 54V DC NOMINAL 4.0Ah 216Wh 60V DC MAX

**Revision Date:** 2018-10-29

**Compiler:** Fengzhao

**Checker:** Dongxuesheng

**Approver:** Zhangxiangjin



Shanghai Research Institute of Chemical Industry Testing Co., Ltd.



# 声 明

## Statement

1. 本报告无本实验室公章无效。  
The report is invalid if it is not affixed the official seal of the laboratory to it.
2. 复制本报告未重新加盖本实验室公章无效。  
Copies of the report without the official seal of the laboratory are invalid.
3. 本报告无编制、审核、批准人签字无效。  
The report is invalid without the signatures of compiler, checker and approver.
4. 本报告涂改无效。  
The report is invalid if it is blotted out.
5. 未经本实验室书面批准，不得部分复制本报告。  
It is forbidden to copy the report partially without the written approval of the laboratory.
6. 送样委托检验结果，仅对所送样品有效。  
The conclusion of the consignment test is only valid for the provided sample.
7. 除另有说明，检测检验类别都是指委托分析。  
Unless noted otherwise, the test type is consignment test.

地址：上海市云岭东路 345 号  
邮政编码(Post Code): 200062  
电话(Tel): (021) 31765555  
网址 (web site): [www.ghs.cn](http://www.ghs.cn)  
电子信箱(E-mail): [fz@ghs.cn](mailto:fz@ghs.cn)

Address: No.345 East Yunling Road, Shanghai  
传真(Fax): (021) 31015117

STIGA S.P.A.

## SAFETY DATA SHEET

Rechargeable Li-ion Battery BT 60 Li 4.0,54V DC NOMINAL 4.0Ah 216Wh 60V DC MAX

## SECTION1 PRODUCT AND COMPANY IDENTIFICATION

**Product name:** Rechargeable Li-ion Battery BT 60 Li 4.0,54V DC NOMINAL 4.0Ah 216Wh 60V DC MAX  
**Company:** STIGA S. P. A.  
**Address:** Via del Lavoro, 6, Castelfranco Veneto (TV) - Italy  
**Email:** Martina Degetto@stiga.com  
**Fax:** +39 0423 450 670  
**Emergency Phone:** +39 0423 450 703  
**SDS Number:** 2618090135  
**SDS Date:** 2018-10-29

## SECTION2 HAZARDS IDENTIFICATION

## Hazards Identification:

Class 9, miscellaneous. The battery has passed the test items of UN Model Regulations, Manual of Test and Criteria Section UN 38.3.

## Emergency Overview:

Caution: Avoid contact and inhalation the electrolyte contained inside the battery.

## SECTION3 INFORMATION ON INGREDIENTS

**Product name:** Rechargeable Li-ion Battery BT 60 Li 4.0,54V DC NOMINAL 4.0Ah 216Wh 60V DC MAX

Ingredient	Concentration	CAS No.	EC No.
Electrolyte salt Lithium hexafluorophosphate	0.05-5%	21324-40-3	244-334-7
Electrolyte solvent, includes one or more of the following:	5-20%		
Ethylene carbonate		96-49-1	202-510-0
Propylene carbonate		108-32-7	203-572-1
Diethyl carbonate		105-58-8	203-311-1
Polyvinylidene Fluoride (PVDF)	<1%	24937-79-9	607-458-6
Copper	3-15%	7440-50-8	231-159-6
Aluminum	2-10%	7429-90-5	231-072-3
Lithium Cobalt Oxide	20-50%	12190-79-3	235-362-0
Graphite	10-30%	7782-42-5	231-955-3

Steel, Nickel and inert components

Balance

/

/

#### SECTION4 FIRST-AID MEASURES

**Skin Exposure:**

If the internal battery materials of an opened battery cell come into contact with the skin, immediately flush with plenty of water.

**Eye Exposure:**

In case of the internal battery materials in contact with eyes, flush with copious amounts of water for at least 15 minutes. Assure adequate flushing by separating the eyelids with fingers. Call a physician.

**Inhalation Exposure:**

If inhaled the internal materials of battery, remove immediately to fresh air and seek medical attention.

**Oral Exposure:**

If swallowed the internal materials of battery, do not induce vomiting. Seek immediate medical attention.

#### SECTION5 FIRE FIGHTING MEASURES

**Extinguishing Media:**

Suitable: Dry chemical, Sandy soil, Carbon dioxide or appropriate foam.

**Firefighting:**

Protective Equipment: Wear self-contained breathing apparatus and protective clothing to prevent contact with skin and eyes.

Specific hazards: Emit toxic fumes under fire conditions.

#### SECTION6 ACCIDENTAL RELEASE MEASURES

**Procedure of Personal Precaution:**

If batteries show signs of leaking, avoid skin or eye contact with the material leaking from the battery. Use chemical resistant rubber gloves and non-flammable absorbent materials for clean up. Mix with inert material (e.g. dry sand, vermiculite) and transfer to sealed container for disposal.

#### SECTION7 HANDLING AND STORAGE

**Handling:**

Keep away from ignition sources, heat and flame. Such batteries must be packed in inner packages in such a manner as to effectively prevent short circuits and to prevent movement which could lead to short circuits. Avoid mechanical or electrical abuse. More than a momentary short circuit will generally reduce the battery service life. Avoid reversing battery polarity within the battery assembly. In case of a battery unintentionally be crushed, rubber gloves must be used to handle all battery components. Avoid contact with eyes, skin. Avoid inhalation. No smoking at working site. Materials to Avoid: Strong oxidizing agents, Corrosives.

**Storage:**

Store in a cool, well-ventilated area. Keep away from ignition sources, heat and flame. Such batteries must be packed in inner packages in such a manner as to effectively prevent short circuits and to prevent movement which could lead to short circuits. Materials to Avoid: Strong oxidizing agents, Corrosives.

**SECTION8 EXPOSURE CONTROL/PPE****Engineering Controls:**

Use ventilation equipment if available. Safety shower and eye bath.

**Personal Protective Equipment:**

Respiratory System: Not necessary under conditions of normal use.

Eyes: Not necessary under conditions of normal use.

Clothing: Wear appropriate protective clothing.

Hand: Safety gloves.

**Other Protect:**

No smoking, drinking and eating at working site. Wash thoroughly after handling.

**SECTION9 PHYSICAL/CHEMICAL PROPERTIES**

**Appearance:** Black plastics cement shell

**Odor:** Odorless

**Melting Point/°C:** >300°C

**Solubility:** Partial slightly soluble in water

**SECTION10 STABILITY AND REACTIVITY****Stability:**

Stable under normal temperatures and pressures.

**Conditions to Avoid:**

Avoid exposure to heat and open flame. Avoid mechanical or electrical abuse. Prevent short circuits. Prevent movement which could lead to short circuits.

**Materials to Avoid:**

Strong oxidizing agents, Corrosives.

**Hazardous Polymerization:**

Will not occur.

**Hazardous Decomposition Products:**

Metal oxides, CO, CO<sub>2</sub>.

**SECTION11 TOXICOLOGICAL INFORMATION****Toxicity Data:**

Not available.

**Irritation Data:**

The internal battery materials may cause irritation to eyes and skin.

**SECTION12 ECOLOGICAL INFORMATION**

No data available.

**SECTION13 DISPOSAL CONSIDERATION****Appropriate Method of Disposal of Substance:**

Lithium batteries are best disposed of as a non-hazardous waste when fully or mostly discharged. Contact a licensed professional waste disposal service to dispose of large quantities materials.

**SECTION14 TRANSPORT INFORMATION**

The battery has passed the test items of UN Model Regulations, Manual of Test and Criteria Section UN 38.3.

**IATA DGR (59<sup>th</sup> Edition):** Proper Shipping Name: Lithium ion batteries  
 UN Number: UN3480  
 Hazard Class: 9  
 The product shall meet the General Requirements and section IA of Packaging Instruction 965.

**IMO IMDG Code (2016 Edition):** Proper Shipping Name: Lithium ion batteries  
 UN Number: UN3480  
 Hazard Class: 9  
 EmS No. : F-A, S-I

### SECTION15 REGULATORY INFORMATION

#### ICAO:

1. Unless be exempted according to ICAO TI, the lithium ion cell/batteries (UN 3480, PI 965) and lithium metal cell/batteries (UN 3090, PI 968) are forbidden for carriage on passenger aircraft.
2. Unless be approved according to ICAO TI, Lithium ion cells/batteries (UN 3480, PI 965) must be offered for transport at a state of charge (SoC) not exceeding 30% of their rated design capacity.
3. A shipper is not permitted to offer for transport more than one (1) package prepared according to Section II of PI 965 and PI 968 in any single consignment. Not more than one (1) package prepared in accordance with Section II of PI 965 and PI 968 may be placed into an overpack.
4. Packages prepared according to Section II of PI 965 and PI 968 must be offered to the operator separately from other cargo and must not be loaded into a unit load device (ULD) before being offered to the operator.

### SECTION16 OTHER INFORMATION

#### Date:

2018-10-29

#### Department:

Shanghai Research Institute of Chemical Industry Testing Co., Ltd.  
 Tel (Fax) : +86-21-52815377/31765555

#### Revision:

0

#### Other Information:

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. We make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigation to determine the suitability of the information for their particular purposes. In no way shall we be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, howsoever arising from using the above information.

