

05559**tesamoll® Standard Schaumstoffdichtung****Produktbeschreibung/ Anwendung:**

tesamoll® Standard I-Profil

Das selbstklebende tesamoll® Standard I-Profil Schaumstoffdichtung für Fenster & Türen ist einfach anzuwenden und schützt vor Zugluft, Kälte, Staub und Lärm. Passt sich optimal verschiedenen Spaltenbreiten an.

- Selbstklebendes und langlebiges Schaumstoffprofil
- Verschließt Spalten von 1 bis 3,5 mm
- Haltbarkeit 4 Jahre
- Weich und flexibel
- Leicht wieder ablösbar
- Verfügbar in weiß und braun
- Verarbeitungstemperatur zwischen 5 °C und 30 °C
- Temperaturbeständig von -50 °C bis +50 °C

tesa SE

Quickbornstr 24
20253 D- Hamburg
Telephone +49-40-49 09 -0
Telefax +49-40-49 09 18 5593

tesa self-adhesive tapes are used successfully in many sectors to solve a variety of problems. Our publications contain numerous examples of such uses, intended to help towards a solution of your particular problems. Each tesa product has been developed for a particular range of applications. Nevertheless, experience has shown that even for one and the same objective, the exact requirements may differ from case to case. We, therefore, recommend that you carry out your own tests in each case, to confirm that the tesa self-adhesive tape which you envisage using is appropriate for your particular application. The Advisory Section of our Technical Service Department will be happy to assist. All information and recommendations are given by us in good faith, on the basis of practical experience, but without warranty.

 tesa SE	Quality management	Produktinformation
Product name and -number: 05559 PI_I profile_d_.doc		

Abmessungen:

Farbe	Länge / Breite / Dicke der Profile
Weiß, braun	6m: 9mm: 4mm

Technische Daten:

Schaum:	PE	Klebkraft/ Stahl	4,8 ±1,4 N/cm
Totale Dicke:	5,2 ± 0,5 mm	Spalten- abdeckung	1 – 3,5 mm
Klebmasse:	Naturkautschuk		

8320 – 02/06