


Technical Data Sheet

Manufacturer name: Besselink Licht Import B.V.			
Address: Nieuwgraaf 10, 6921 RJ DUIVEN, THE NETHERLANDS			
Model identifier: L221501-35			
Type of light source: LED bulb (Self-ballasted LED-lamps)			
Lighting technology used:	LED	Non-directional or directional:	Non-directional
Light source cap-type (or other electric interface)	E27		
Mains or non-mains:	Mains	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	No
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Yes
Product parameters			
Parameter	220-240 V~, 50 Hz, 3 W, 1800 K, 80 lm, dimmable		
General product parameters:			
Energy consumption in on-mode (kWh/1 000 h)	3 W	Energy efficiency class	Exempt
Useful luminous flux (Φ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	80 lm (Φ_{use})	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	1800 K
On-mode power (P_{on}), expressed in W	3 W	Standby power (P_{sb}), expressed in W and rounded to the second decimal	N/A

Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal		N/A	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	≥80
Outer dimensions without separate control gear, lighting control parts and non-lighting control parts, if any (millimeter)	Height	16cm	Spectral power distribution in the range 250 nm to 800 nm, at full-load	
	Width	14cm		
	Depth	14cm		
Claim of equivalent power ⁽³⁾		Yes	If yes, equivalent power (W)	Incandescent: 10 W
			Chromaticity coordinates (x and y)	0,533; 0,410
Parameters for directional light sources:				
Peak luminous intensity (cd)		N/A	Beam angle in degrees, or the range of beam angles that can be set	N/A
Parameters for LED and OLED light sources:				
R9 colour rendering index value		N/A	Survival factor	0.9
the lumen maintenance factor		0.96		
Parameters for LED and OLED mains light sources:				
displacement factor ($\cos \varphi_1$)		0.9	Colour consistency in McAdam ellipses	N/A
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.		N/A	If yes then replacement claim (W)	N/A
Flicker metric (Pst LM)		N/A	Stroboscopic effect metric (SVM)	N/A